

Water repellent
for construction

SI1200Z



FEATURES

- Water dilutable

BENEFITS

- Wonderful surface repellency
- Penetrating and breathable
- Protecting against penetrating damp
- Easy to use
- Reducing spallation due to freeze-thaw and efflorescence, thereby increasing the life of the substrate

COMPOSITION

- Silicone

1. Product Description

SI1200Z Water repellents for construction are effective, easy-to-use silicone emulsions.

2. Applications

For use on mineral substrates such as brick, clay, stone, concrete and mortar that require water repellency

3. Key Performance Properties

Good storage stability with no creaming or severe oiling.

Good dilution stability

Making eternal water repellent layer

4. Typical Property Data

Property	Test method	SI1200Z
Appearance	ASTM E1767-04	Milky white liquid
Viscosity (cP, 25 °C)	ASTM D4016-02	1 ~ 30
Active content(%)	-	7
Diluent	-	Water

※ Typical properties should not be used as specifications
They are evaluated in laboratory, and can be differ from test condition.

Water repellent
for construction

SI1200Z



5. How To Use

- SI1200Z Emulsions are used in a wide variety of applications because of their intermediate viscosity and water-dilutable, stable forms.
- As water repellent, these emulsions may be applied in low concentrations by spraying, dipping, brushing or wiping.

a. Surface Preparation

- Remove any dust, humidity, oil and other contaminants from surface to be coated.
- Concrete : Must be cured at least 28 days at 20°C/68°F and below 80% R.H.
Moisture content of the concrete surface must be below 6%.

b. Application Condition

- The surface must be completely clean and dry.
- Do not apply when relative humidity is above 80%.
- The surface temperatures must be at least 3°C (5°F) above dew point to prevent condensation.

c. Thinning Do not dilute.

d. Method of Application Brush, Roller and spray application.

e. Film Thickness Recommended per coat 8 microns dry.
Two coats are recommendable.

f. Recoating Interval At 20°C/68°F, minimum : 2 hours

6. Handling Precautions

- For the purpose of water protective, avoid to apply it where is stagnated for a long time or any place being affected by water pressure.
 - Store in original unopened containers in a dry place. Temperature should not exceed 30 °C for prolonged periods.
 - Keep in place that child's hand does not touch and never ingest or do not touch in skin.
 - Keep or do work at neighborhood of heat or fire.
 - Do not use besides service.
 - Do not inflict shock in receptacle.
 - Avoid direct ray of light and keep in state that is tightly shut in place that moisture is less.
 - Do not mixing with other products.
 - Wash cleanly after work.
 - Abolish through waste processing company.
 - As change in quality can be at long term storage, use in validity.
 - Handle according to good industrial hygiene practice.
 - The material safety data sheet is available from your KCC representative, or distributor, or by writing to KCC customer service, or by calling 82-31-288-3228
- ※ Inquire other questions to customer service.
※ When there is something wrong to product, it compensated by compensation regulation.

Water repellent
for construction

SI1200Z



7. Safety and Storage

- SI1200Z, Water repellents for construction have a usable life at least of 12 months from date of manufacture.
- Keep out of the reach of the children.

8. Packaging

18 L / Pail

9. Warranty Information – *Please read carefully*

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that KCC's products are safe, effective, and fully satisfactory for the intended end use.

KCC's sole warranty is that the product will meet the KCC sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to replacement of any product shown to be other than as warranted.

KCC specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Unless KCC provides you with a specific, duly signed endorsement of fitness for use, KCC disclaims liability for any incidental or consequential damages.

Suggestions of use shall not be taken as inducements to infringe any patent.

10. The date of issue

2011.05.17

- ※ Please refer to MSDS if you want to know more specific usage or caution.
for further information, please see our website, www.kccworld.co.kr